




LOCKABLE XL ANTI-RATTLE HITCH PIN



DO NOT CROSS THE THREADS. All pins and brackets are checked before packaging and cross-threaded pins will not be warrantied.

These longer XL pins have a 5 inch "effective length" for most non-standardized hitches

Apply a small amount of grease to the threads. Follow illustrations below

Use a 15/16 inch wrench or socket & driver to tighten the pin to **30 foot lbs** (or 40NM) MAX.


Pin can be locked with a standard 1/4 inch padlock (not included), or secured with the supplied clip.

Bracket arms can be spread if needed to prevent moving inside of the hitch tube.


XL pins will work with 2.5" and 3" hitches with reducers (not included), as well as most non-standardized boxed in hitches with 4 inch outer "walls". Be aware of the length of the pin.

Be sure to tighten the pin to spec. Over-tightening pins on non-standardized hitches can lead to a bend in the outer walls. North Shore Racks Inc. is not responsible for any damage that may occur from over-tightening.

2




3




***Hand tighten to begin
DO NOT CROSS THREADS**

1



4



**USE 15/16 INCH WRENCH OR
SOCKET & DRIVER
(DO NOT USE ADJUSTABLE WRENCH)**
Tighten the pin to **30 foot lbs** (or 40NM)